iZone CHPL Care and Maintenance

Simple Care. Lasting Appearance.

Keep your iZone Imaging CHPL graphic panels looking their best with routine cleaning and the right maintenance practices. Start with the mildest cleaning method and use gentle, nonabrasive tools to protect the surface finish.

Everyday Cleaning

Most routine cleaning requires only mild soap, warm water, and a soft cloth.

1. Remove loose dust, dirt, and grit before wiping to help prevent scratches.
2. Clean with a mild soap-and-water solution using a soft, nonabrasive cloth.
3. Rinse with clean water to remove soap residue.
4. Dry with a clean, soft cloth to minimize streaks and water spots.

Clean spills and marks promptly whenever possible.

Graffiti and Stubborn Stains

iZone exterior-grade CHPL panels are chemically durable and can be cleaned with solvent-based products containing volatile organic compounds (VOCs) to remove graffiti and stubborn stains.

Remove loose dirt and grit before cleaning and test the cleaner on a sample or inconspicuous area first. Apply it with a soft, nonabrasive cloth. Follow with a mild soap-and-water wash, rinse thoroughly, and dry.

Follow the cleaner manufacturer's safety instructions, provide adequate ventilation, and never mix cleaning products. These recommendations apply to exterior-grade CHPL; contact iZone Imaging for guidance on interior grades.

If a stain persists, contact iZone Imaging. Provide the panel finish, type of stain, and cleaners already used so we can recommend the next step.

Protect the Finish

- Avoid steel wool, scouring pads, abrasive powders, and hard-bristle brushes.
- Do not use razor blades or metal scrapers to remove deposits.
- Avoid aggressive rubbing, sanding, or polishing that could change the surface sheen.
- On 0.040" laminate bonded to a substrate, avoid flooding seams and exposed substrate edges.

Edge Care

Exposed compact laminate edges may receive an optional cosmetic treatment to help maintain their color and appearance. Edge treatments are intended to maintain appearance and are not required for panel longevity or warranty coverage. Keep waxes and sealants off the graphic face unless specifically approved by iZone.

Scratches and Surface Damage

Cleaning cannot repair deep scratches, chips, or burns. Before applying automotive polishes, scratch removers, or surface-restoration products, contact iZone Imaging. These treatments may change the sheen or create a visible difference in the finish.

A Little Care Goes a Long Way

Regular cleaning and prompt attention to stains help preserve the appearance of your iZone CHPL panels throughout their service life.

Need help with a stubborn stain? Contact iZone Imaging with photos and your panel information for cleaning guidance.